


### WINCH

Single or Dual  
8,000 lb. winch



### BODY

Modular aluminum construction,  
designed to provide years of service  
and ease of maintenance

### UNDERLIFT

Self-loading 4,000 lb.  
lift capacity with  
hydraulic L-arms that  
feature mechanical  
LOCKLINK® technology



## SPECIFICATIONS

### ENGINEERED FOR **STRENGTH AND DURABILITY**

The MPL-40 Light Duty Integrated Wrecker is an 8 ton wrecker that features a 2-stage recovery boom, 4,000 lb. self-loading underlift, Underlift Level Stop System® and a modular aluminum body.

#### RECOVERY BOOM: 2-STAGE

Retracted Capacity @ 30°	16,000 lbs.
Extended Capacity @ 30°	6,000 lbs.
Maximum Hook Height	110 in.
Maximum Boom Angle	32°

#### REACH PAST TAILBOARD

Reach Past Tailboard - Extended @ 0°	67 in.
Reach Past Tailboard - Extended @30°	46 in.

#### UNDERLIFT BOOM

Retracted Rating	4,000 lbs.
Retracted Reach	52 in.
Extended Rating	4,000 lbs.
Extended Reach	81 in.
Positive Tilt	20°
Negative Tilt	20°
Tow Capacity	7,500 lbs.

#### WINCH

Winch Capacity	8,000 lbs.
Winch Options	Single or Dual
Wire Rope (EIPS Galvanized)	3/8 in. x 110 ft. (Optional Swivel Hook)
Minimum GVW Rating	11,000 lbs.
Minimum Cab-to-Axle, CA	60 in.

#### CHASSIS

Minimum GVW Rating	11,000 lbs.
Minimum Cab-to-Axle, CA	60 in.

BECAUSE THE  
WORK **DEMANDS** IT.

Want a truck that works as hard as you do?

Visit our website at [Jerrdan.com](http://Jerrdan.com) to find your nearest distributor.

# LIGHT DUTY WRECKER

## INTEGRATED MPL-40

FEATURES	STANDARD	OPTIONAL
<b>CONTROLS</b>		
Dual Side Manual Controls	•	
Wired Winch Remote Control	•	
Wireless Winch Remote Control		•
<b>BODY</b>		
No-Lube™ Technology	•	
Greaseable Joints w/ Grease Fittings		•
Lighted Driver Side Toolbox	•	
Polished Aluminum Rubrails	•	
Aluminum Diamond Plate Decking	•	
Lighted Passenger Side Tool Box	•	
24 in. Aluminum Tunnel Box	•	
<b>LIGHTING &amp; ELECTRICAL</b>		
DOT Lighting	•	
Backup Alarm	•	
Fold Down Light Bar Mount		•
In-Cab Switch Panel		•
LED Work Lights Upper/Lower		•
LED Lightbar		•
Backup Camera Kit		•
Aluminum Light Pylon		•
<b>BOOM &amp; WINCHES</b>		
8,000 lb. Boom w/ Dual Lift Cylinders	•	
Self-loading Wheel Grids w/ LOCKLINK®	•	
Underlift Level Stop Assist System	•	
Remote Free Spool Handles	•	
Single 8,000 lb. Worm Gear Winch with Tensioner Plate and Free Spool	•	
Dual Worm Gear Winches with Tensioner Plate and Free Spool		•
Tailboard D-Ring Options		•

FEATURES	STANDARD	OPTIONAL
<b>TOWING ACCESSORIES</b>		
Wheel Lift Tie-Down Straps	•	
Fifth Wheel Plate		•
Tow Sling		•
Tow Sling Mounting Brackets		•
Gooseneck Trailer Attachment		•
Spade Foot Attachment		•
Low Angle Recovery Sheave w/ Hydraulic Tilt Lockout Valve		•
Motorcycle Attachment		•
Aluminum Dollies		•
Trailer Ball Attachments (Available in sizes: 1 7/8 in., 2 in., 2 5/16 in.)		•
Manual L-Arm Wheel Grids		•