

2025 Chevrolet BrightDrop 600 AWD

Specifications & Highlights



VEHICLE

GVWR ¹	9,990 lbs. (11,000 lbs. optional)
Exterior dimensions (without mirrors)	290 in. L x 86.5 in. W x 108.8 in. H
Rear cargo access dimensions	57.6 in. W x 73.4 in. H

Max. cargo volume ²	614.7 cu. ft.
Minimum ground clearance	7.5 in.
Available max. payload ³	3,130 lbs. ⁴

PERFORMANCE

Peak charge rate	Up to 160 miles of range per hour ⁵ (120-kW DC Fast Charging)
Available GM-est. max. range	Up to 303 mi. (city), 234 mi. (highway), 272 mi. (combined) ⁶
GM-est. standard range	Up to 200 mi. (city), 152 mi. (highway), 179 mi. (combined) ⁷

LIMITED WARRANTIES

3 years/36K miles Bumper to Bumper ⁸
8 years/100K miles Electrification ⁸
6 years/100K miles Rust-Through Corrosion Coverage ⁸



SAFETY

Standard safety and driver assistance features⁹:

Adaptive Cruise Control	Front Pedestrian and Bicyclist Braking
Blind Zone Steering Assist	HD Surround Vision
Enhanced Automatic Emergency Braking	IntelliBeam auto high beams
Following Distance Indicator	Intersection Automatic Emergency Braking
Forward Collision Alert	Lane Keep Assist with Lane Departure Warning
Front and Rear Park Assist	Rear Cross Traffic Braking

Chevrolet Brightdrop 600 preproduction model shown with optional equipment. Production model may vary.

¹ Maximum Gross Vehicle Weight Rating (GVWR). When properly equipped; includes weight of vehicle, passengers, cargo and equipment. ² Cargo capacity limited by weight and distribution. ³ These maximum payload ratings are intended for comparison purposes only. Before you buy a vehicle or use it to haul people or cargo, carefully review the Vehicle Loading section of the Owner's Manual and check the carrying capacity of your specific vehicle on the label on the inside of the driver's door jamb. ⁴ Requires 11,000-lbs. GVWR. ⁵ Requires public DC Fast Charger and available Max Range battery pack. Actual charge times will vary based on battery starting state of charge, battery condition, output of charger, vehicle settings and outside temperature. See the vehicle Owner's Manual for additional limitations. ⁶ Requires 2025 Chevrolet BrightDrop 400/600 with optional Max Range battery pack. GM estimate based on a full charge and subject to change prior to production. GM-estimated range based on current capability of analytical projection consistent with SAE J1634 revision 2017 - MCT. Actual range may vary based on several factors, including temperature, terrain, battery age, loading, and how you use and maintain your vehicle. ⁷ GM estimate based on a full charge and subject to change prior to production. GM-estimated range based on current capability of analytical projection consistent with SAE J1634 revision 2017 - MCT. Actual range may vary based on several factors, including temperature, terrain, battery age, loading, and how you use and maintain your vehicle. ⁸ Whichever comes first. See dealer for details. ⁹ Safety or driver assistance features are no substitute for the driver's responsibility to operate the vehicle in a safe manner. The driver should remain attentive to traffic, surroundings and road conditions at all times. Visibility, weather, and road conditions may affect feature performance. Read the vehicle Owner's Manual for more important feature limitations and information.

BrightDrop has taken reasonable steps to ensure information presented is accurate. However, BrightDrop reserves the right to make changes to this without notice. Please consult the Vehicle Order Guide for the latest information.

2025 Chevrolet BrightDrop 600 AWD

Specifications



EXTERIOR

Wheelbase	183 in.
Overall length	290 in.
Overall width without mirrors	86.5 in.
Overall width with mirrors	106.2 in.
Overall height	108.8 in.
Overall height with mast antenna	117.6 in.
Turning diameter, curb-to-curb	51.5 ft.
Minimum ground clearance	7.5 in.
Front overhang	34 in.
Rear overhang	72.6 in.
Curbside step, height to ground	15.5 in.
Rear step bumper, height to ground	18 in.
Approach angle	23.2 degrees
Departure angle	12.6 degrees

INTERIOR

Max. cargo volume ¹	614.7 cu. ft.
Cargo area dimensions with door closed	168.9 in. L x 83.7 in. W x 82 in. H
Rear cargo access dimensions with door open	57.6 in. W x 73.4 in. H
Internal cargo area height, door closed	82 in.
Internal cargo area height, door open	76 in.
Curbside door opening width	36.7 in.
Bulkhead access dimensions with door open	75.8 in. H x 28.2 in. W
Cargo floor, height to ground	26.4 in.

PERFORMANCE

Available GM-est. max. range	Up to 303 mi. (city), 234 mi. (highway), 272 mi. (combined) ²
GM-est. standard range	Up to 200 mi. (city), 152 mi. (highway), 179 mi. (combined) ³
Peak charge rate	Up to 160 miles of range per hour ⁴ (120-kW DC Fast Charging)

¹ Cargo capacity limited by weight and distribution. ² Requires 2025 Chevrolet BrightDrop 400/600 with optional Max Range battery pack. GM estimate based on a full charge and subject to change prior to production. GM-estimated range based on current capability of analytical projection consistent with SAE J1634 revision 2017 - MCT. Actual range may vary based on several factors, including temperature, terrain, battery age, loading, and how you use and maintain your vehicle. ³ GM estimate based on a full charge and subject to change prior to production. GM-estimated range based on current capability of analytical projection consistent with SAE J1634 revision 2017 - MCT. Actual range may vary based on several factors, including temperature, terrain, battery age, loading, and how you use and maintain your vehicle. ⁴ Requires public DC Fast Charger and available Max Range battery pack. Actual charge times will vary based on battery starting state of charge, battery condition, output of charger, vehicle settings and outside temperature. See the vehicle Owner's Manual for additional limitations.