2026 Chevrolet BrightDrop 600 AWD

Specifications & Highlights

VEHICLE

GVWR ¹	9,990 lbs. (11,000 lbs. optional)
Exterior dimensions (without mirrors)	290 in. L x 86.5 in. W x 108.8 in. H
Rear cargo access dimensions	57.6 in. W x 73.4 in. H

Max. cargo volume ²	614.7 cu. ft.
Minimum ground clearance	7.5 in.
Available max. payload ³	3,130 lbs. ⁴

PERFORMANCE

Peak charge rate	Up to 180 miles of range per hour ⁵ (120-kW DC Fast Charging)
GM-est. range (available Max Range battery pack)	Up to 322 mi. (city), 242 mi. (highway), 286 mi. (combined) ⁶
GM-est. range (available Extended Range battery pack)	Up to 230 mi. (city), 172 mi. (highway), 204 mi. (combined) ⁷
GM-est. standard range	Up to 199 mi. (city), 148 mi. (highway), 176 mi. (combined) ⁸

LIMITED WARRANTIES

years/36K miles Bumper to Bumper ⁹
years/100K miles Electrification ⁹
vears/100K miles Rust-Through Corrosion Coverage ⁹



envolve

Chevrolet Brightdrop 600 preproduction model shown with optional equipment. Production model may vary.

vehicle, passengers, cargo and equipment. 2 Cargo capacity limited by weight and distribution vehicle or use it to haul people or cargo, carefully review the Vehicle Loading section of the Owner' door jamb. 4 Requires 11,000-lbs. GVWR. 5 Requires public DC Fast Charger and available Max Range battery pack. Actual charge times will vary based on battery starting state of charge, battery condition output of charger, vehicle settings and outside temperature. See the vehicle Owner's Manual for additional limitations. **6** Requires 2026 Chevrolet BrightDrop 400/600 with optional Max Range battery pack. GM estimate based on a full charge and subject to change prior to production. GM-estimated range based on pack. GM estimate based on a full charge and subject to change prior to production. GM-estimated range based vehicle. 9 Whichever comes first. See dealer for details. 10 Safety or driver assistance features are no substitute for the and road conditions at all times. Visibility, weather, and road conditions may affect feature performance. Read the vehicle Owner's Manual for more important feature limitations and information.

BrightDrop has taken reasonable steps to ensure information presented is accurate. However, BrightDrop reserves the right to make changes to this without notice. Please consult the Vehicle Order Guide for the latest information.

F6: March 2025

SAFETY

Standard safety and driver assistance features¹⁰:

Adaptive Cruise Control	Front Pedestrian and Bicyc
Blind Zone Steering Assist	HD Surround Vision
Enhanced Automatic Emergency Braking	IntelliBeam auto high beam
Following Distance Indicator	Intersection Automatic Em
Forward Collision Alert	Lane Keep Assist with Lane
Front and Rear Park Assist	Rear Cross Traffic Braking

ront Pedestrian and Bicyclist Braking ID Surround Vision ntelliBeam auto high beams ntersection Automatic Emergency Braking ane Keep Assist with Lane Departure Warning

Rear Vision Camera Reverse Automatic Braking Safety Alert Seat Traffic Sign Recognition

2026 Chevrolet BrightDrop 600 AWD

Specifications



EXTERIOR

Wheelbase	183 in.
Overall length	290 in.
Overall width without mirrors	86.5 in.
Overall width with mirrors	106.2 in.
Overall height	108.8 in.
Overall height with mast antenna	117.6 in.
Turning diameter, curb-to-curb	51.5 ft.
Minimum ground clearance	7.5 in.
Front overhang	34 in.
Rear overhang	72.6 in.
Curbside step, height to ground	15.5 in.
Rear step bumper, height to ground	18 in.
Approach angle	23.2 degrees
Departure angle	12.6 degrees

INTERIOR

Max. cargo volume¹	614.7 cu. ft.
Cargo area dimensions with door closed	168.9 in. L x 83.7 in. W x 82 in. H
Rear cargo access dimensions with door open	57.6 in. W x 73.4 in. H
Internal cargo area height, door closed	82 in.
Internal cargo area height, door open	76 in.
Curbside door opening width	36.7 in.
Bulkhead access dimensions with door open	75.8 in. H x 28.2 in. W
Cargo floor, height to ground	26.4 in.

PERFORMANCE

GM-est. range (available Max Range battery pack)	Up to 322 mi. (city), 242 mi. (highway), 286 mi. (combined) ²
GM-est. range (available Extended Range battery pack)	Up to 230 mi. (city), 172 mi. (highway), 204 mi. (combined) ³
GM-est. standard range	Up to 199 mi. (city), 148 mi. (highway), 176 mi. (combined)⁴
Peak charge rate	Up to 180 miles of range per hour⁵ (120-kW DC Fast Charging)