

REFRIGERATED

KOLD KING

When transporting perishable cargo, you need a solution that protects your products and maximizes operating efficiencies: the Kold King. Available in a variety of sizes, it can be adjusted from single- and mid-temperature to deep-frozen, multi-temperature applications. Thermally efficient, customizable, and built to stand up to the rigorous demands of multi-stop refrigerated delivery, the Kold King is a smart choice for transporting a variety of products.



(Shown with optional insulated double-narrow swing rear doors and reefer access steps)



Dairy



Flowers



Fruit



Ice



Ice Cream



Meat



Seafood

Features

- **Minimize front wall damage** with a durable, insulated FiberPanel® PW (FRP) front wall
- **Protect the environment while protecting your cargo** with the most environmentally friendly, thermally efficient polyurethane foam in the industry
- **Protect rear entry and ease cleaning** with a solid, 10-gauge steel, one-piece molded V-groove threshold
- **Enhance impact resistance and durability** with a 12-gauge galvanized-steel floor perimeter reinforcing rub rail

Options

- **Increase corrosion resistance and durability** with a stainless-steel rear frame and stainless-steel front verticals
- **Customize your truck body** with a wide range of bumpers, side and rear doors, and additional insulation
- **Get your truck quicker** with Supreme's in-house reefer installation
- **Customize insulation levels** to meet your cargo needs



(Shown with optional reefer unit and reefer access steps)

Available Sizes

Width	Length	Height			
		79"	85"	91"	97"*
96"	12'	•	•	•	
	14'	•	•	•	
	16'	•	•	•	•
	18'		•	•	•
	20'		•	•	•
	22'		•	•	•
102"	24'		•	•	•
	18'		•	•	•
	20'		•	•	•
	22'		•	•	•
	24'		•	•	•

- Available sizes limited by chassis type
- Requires approval from chassis OEM

KOLD KING CAB CHASSIS

AVAILABLE SIZES

Width	Length	Height					
		79"	85"	91"	97"	103"	109"
96"	12'	●	●	●			
	14'	●	●	●			
	16'	●	●	●	●		
	18'		●	●	●		
	20'		●	●	●	●	
	22'		●	●	●	●	●
	24'		●	●	●	●	●
	26'			●	●	●	●
	28'			●	●	●	
102"	18'		●	●	●		
	20'		●	●	●	●	
	22'		●	●	●	●	●
	24'		●	●	●	●	●
	26'			●	●	●	●
	28'				●	●	●

• Available sizes limited by chassis type

FEATURES

Side Walls	<ul style="list-style-type: none"> • .040" Smooth aluminum pre-painted white panels • Galvanized-steel Z-wall posts with spruce/pine/fir build ups
Front	<ul style="list-style-type: none"> • Insulated FiberPanel® PW (FRP) front wall • Molded-composite front corner wind deflector with fiberglass dormer • Extruded-aluminum radius vertical front corners
Lining	<ul style="list-style-type: none"> • .090" Seamless glass board lining on side walls and ceiling
Insulation	<ul style="list-style-type: none"> • 3" Polyurethane foam – side walls, ceiling, above cross members in floor • 4" Polyurethane foam – front wall
Rear Frame	<ul style="list-style-type: none"> • Painted galvanized steel • 14 ga. Header • 12 ga. Corner posts • 10 ga. One-piece V-groove threshold • Aluminum drip rail over rear door • Internal gussets
Rear Door	<ul style="list-style-type: none"> • Medium-temp insulated roll-up • Safety release and lockable hasp
Floor	<ul style="list-style-type: none"> • Smooth box-type extruded-aluminum (no subfloor) • Four Kazoo drains
Subframe	<ul style="list-style-type: none"> • 3" I-beam cross members on 12" C/L • 4" I-beam longills • Full-perimeter steel reinforcing aluminum rub rail • .060" Seamless fiberglass splash pan above cross members • Pre-coated understructure
Roof	<ul style="list-style-type: none"> • One-piece .032" aluminum skin • Galvanized-steel roof bows on 24" C/L
Interior Lights	<ul style="list-style-type: none"> • LED dome light with rear switch - hot wired
Exterior Lights	<ul style="list-style-type: none"> • LED clearance lights • Existing chassis taillights
Bumper	<ul style="list-style-type: none"> • Pooched ICC
Additional Features	<ul style="list-style-type: none"> • Two rear grab handles
Warranty	<ul style="list-style-type: none"> • 1-year white surface and leaks • 3-year/36,000-mile limited bulkhead-to-bumper warranty • 5-year limited structural warranty (roof, wall and floor structure) • See our warranty policy for details

AVAILABLE OPTIONS

Side Walls	<ul style="list-style-type: none"> • Aluminum contoured rubrail (hat section)
Front	<ul style="list-style-type: none"> • Insulated bulkhead (2", 3", 4") - movable and stationary • Polished-aluminum cast front corners
Lining	<ul style="list-style-type: none"> • 1/4" FiberPanel® PW (FRP) • ArmorTuf®-NXT
Scuff	<ul style="list-style-type: none"> • Smooth or corrugated in galvanized steel • Smooth or corrugated in aluminum
Insulation	<ul style="list-style-type: none"> • 4" Polyurethane foam (walls, ceiling, floor) • 5" Polyurethane foam (walls, ceiling, floor) • 6" Polyurethane foam (ceiling, floor - between cross members only)
Side Door	<ul style="list-style-type: none"> • Single-swing • Double-swing
Rear Frame	<ul style="list-style-type: none"> • Stainless-steel
Rear Door	<ul style="list-style-type: none"> • Low-temp insulated roll-up • Full-opening swing • Three-panel full-opening swing
Steps	<ul style="list-style-type: none"> • Stirrup • Pull-out RV • Bustin slide-away • Insulated aluminum recessed stepwell
Floor	<ul style="list-style-type: none"> • Anti-skid box-type reefer • Anti-skid inverted "T" • Additional Kazoo floor drains • Wheel wells • Forklift reinforcement (18' and longer)
Ramp	<ul style="list-style-type: none"> • Aluminum slider (10', 12', 14', 16')
Interior Lights	<ul style="list-style-type: none"> • Additional LED dome light
Cargo Control	<ul style="list-style-type: none"> • E-Track • F-Track • Rope ties • Floor ties
Bumpers	<ul style="list-style-type: none"> • Full-width pooched ICC • Full-width two-step pooched ICC • One-way pooched step • Full-width pooched step • Chicago-style step • Rubber dock
Accessories	<ul style="list-style-type: none"> • Hitch receiver • Rear spot-view mirror - stainless steel • Back-up camera • Back-up alarm • Tire chocks • Reflector Kit • Fire extinguisher • First aid kit
Liftgate	<ul style="list-style-type: none"> • Contact a Supreme Sales Representative for available options

Due to Supreme Corporation's commitment to product improvement and quality, specifications and options are subject to change without notice.

REASONS TO BELIEVE

The Supreme Difference



Innovation at the Forefront

Many of our vehicles are made with our own, specialized FiberPanel® material – available with both a plywood inner core (PW (FRP)) or a lightweight, honeycomb core (HC) – in our state-of-the-art Tower Structural Laminating (TSL) facility using an innovative, patented manufacturing process.



National Presence

Wherever you're located in the U.S., you're always near a Supreme Corporation representative. With seven manufacturing facilities throughout the United States, we can help you find the right truck body to meet your requirements, no matter where you are.



Warranty Policy

We offer one of the best warranties in the business. Our 1-year limited warranty covers white surface and leaks. Our 3-year/36,000-mile limited bulkhead-to-bumper warranty covers repairs and replacement in the event a part is found to be defective. In addition, a 5-year limited structural warranty (roof, wall, and floor structure) lets you know your Supreme truck body is built to last. For additional information, please review our warranty policy.

