

American
c a r g o



BY
MIDWAY
Specialty Vehicles, LLC

MVP

NTEA MEMBER VERIFICATION PROGRAM

Distinguished MVP member 2017-2020



GMC

BUSINESS
ELITE

CONTACT: DAN GLEASON
800-505-2530
574-606-7026
DGLEASON@MYMIDWAY.COM

STANDARD FEATURES
ALUMINUM I BEAM ON 16" CENTERS
ICC BUMPER
HEAVY DUTY CAST ALUMINUM CORNERS
ANTI-SNAG ROOF BOWS ON 16" CENTERS
SIDES FULLY LINED WITH 3/8" PLYWOOD
DOME LIGHT WITH SWITCH
TWO GRAB HANDLES AT REAR
THRESHOLD FLUSH WITH DRAIN TROUGH
2 X 6 SHIPLAP PINE FLOOR
FULLY UNDERCOATED

ADDITIONAL STANDARD FEATURES

040 SMOOTH ALUMINUM EXTERIOR
 LED MARKER LIGHTS
 PREMIUM ROLL-UP DOOR WITH SPRING SILENCER
 STAINLESS STEEL RIVETS ON ROLL-UP DOOR
 3 INCH STEEL I-BEAM CROSSMEMBERS
 FULL INTERNAL PERIMETER RAIL OF 12GA. STEEL

FRP BULKHEAD
 ANTI-SAIL MUB FLAPS
 GALVANEAL STEEL REAR STRUCTURE
 DRAIN TROUGH ON REAR THRESHOLD
 5 INCH HEAVY-DUTY ALUMINUM RUB RAIL
 6 INCH SET BACK ON ALL E SERIES CHASSIS

AVAILABLE OPTIONS

SLIDING BULKHEAD DOOR
 TIE DOWN RINGS
 E-TRACK
 HARDWOOD SLATS
 2 X 6 INCH DENSE PINE FLOOR
 36 & 48 INCH CAB OVER
 VARIOUS SIDE & REAR DOOR OPTIONS
 PULL-OUT RAMPS
 LIFT GATES
 BACK UP CAMERA SYSTEM

FRP WALLS
 INSULATION
 POWER & MANUAL VENTS
 A/C & HEATING IN CARGO AREA
 WINDOWS
 TRANSLUCENT ROOF
 FULL WIDTH POOCHED STEP BUMPER
 VARIOUS SHELVING CONFIGURATIONS
 CUSTOM LENGTHS, WIDTHS & HEIGHTS

BOX LENGTH	10'	12'	14'	15'	16'
INTERIOR HEIGHT	78	78	84	84	84
A) WHEEL BASE	139	139	159	176	176
B) OVERALL HEIGHT	113	113	123	123	123
C) OVERALL LENGTH	229	253	277	289	301
D) EXTERIOR BOX LENGTH	131	155	179	191	203
E) USABLE LOAD LENGTH	123	147	171	183	195
F) EXTERIOR BOX WIDTH	80	80	96	96	96
G) USABLE LOAD WIDTH	79	79	92	92	92
H) DOOR OPENING WIDTH	72	72	88	88	88
I) DOOR OPENING HEIGHT	71	71	77	77	77
J) GROUND TO BUMPER	21	21	21	21	21
K) GROUND TO FLOOR	33	33	38	38	38
L) BUMPER TO FLOOR	13	13	18	18	18



BUSINESS
 ELITE

** THESE MEASUREMENTS ARE APPROXIMATE ** AND CAN CHANGE BASED ON CHASSIS FRAME, TIRES, AND OTHER INCIDENTALS IN THE EVENT THAT YOU HAVE A CRITICAL HEIGHT RESTRICTION, PLEASE DISCUSS WITH YOUR SALESPERSON FOR WHEEL WELL TRUCKS, SUBTRACT 4" FROM I, J, AND K.

